



Gibus[®]
THE SUN FACTORY · ITALY

OUTDOOR BLINDS / STRAIGHT DROP AWNINGS

TOLO

Gibus Australia
www.gibus.com.au



Tolo represents the ongoing commitment to innovation and quality design that Gibus is renowned for. The series comprises of three models, each offering a solution that can be integrated seamlessly with facades and structures.

The awnings feature a unique cylindrical pelmet, which houses and protects the fabric when retracted. When opening the awnings the front bar descends effortlessly and connects with magnetic feet for a secure hold. For additional stability stainless steel cable guides or aluminium side channels are available.



DIMENSIONS

Min Width	1,200mm	Min Height	2,000mm
Max Width	4,800mm	Max Height	3,500mm

OPTIONS



FEATURES & BENEFITS

- 3 styles available - choose the best option to suit your requirements & installation area.
- Motorised (240v tubular motor) with remote control
- Unique patented magnetic feet - cradle & strongly secure the front bar in position when closed.
- Magnetic feet available in 3 configurations - fix to railing/floor, recess or wall face.
- Provides privacy whilst offering protection from wind, rain, heat & glare.
- Assists in regulating temperature - reduces sun penetration & absorbs heat to keep areas cooler in Summer.
- Ability to protect large outdoor areas - multiple awnings can be connected & operate in sync.
- Ability to be partially or fully retracted as required.
- Tolo GA (side guides) - has an innovative locking system inside the channels which can stop the awning in stable intermediate positions.
- When retracted the fabric is protected by a stylish colour matched cylindrical pelmet.
- Wide range of fabrics available including block out/privacy & clear PVC.
- Powder coat finishes available for aluminium pelmet, front bar & side channels – durable with superior colour retention.
- Tested to withstand winds that exert a maximum pressure of 110Nm or similar to a persistent wind speed of 49km/hr.
- 5 year manufacturers warranty.



Left to right: 1. CL magnetic foot with front bar 2. Floor/railing fixed 3. Recess fixed 4. Wall fixed